



uriSTRONG^{NEW} LIME AND URINE SCALE REMOVER

Ideal cleaner for very heavy and persistent calcification in sanitary areas

Product description:

Use as a concentrate for very strong calcification; can be applied to stainless steel

Results:

The product dissolves and removes lime and urine scale, boiler scale and other mineral deposits such as rust, cement, concrete and mortar remains.

Directions for use of uriSTRONG:

Clean the surface of urinals and toilets, removing organic substances such as fat, oil and paper. Flush with plenty of water (warm water increases effectiveness). Use uriSTRONG at a concentration of 5-10%. Exposure time is 5-30 minutes. For very strong deposits you may increase the dosage. This product can be applied to stainless steel. Ensure that uriSTRONG does not come into contact with chrome fittings or metals such as aluminum or non-ferrous metals. May cause discoloration. Not suitable with marble. By uridan urinals lift the cover before use.

Areas of application:

Toilets and urinals, boilers, heat exchangers, etc.

Ingredient declaration:

Contains orthophosphoric acid

Dosage:

Place of application	Concentration in %	Temperature	Exposure time
Urinals, Toilets	5 - 10	35 - 55 °C	5 - 30 Min.
Heat exchanger	5 - 10	35 - 55 °C	Rinse through
Boilers	5 - 20	35 - 55 °C	Rinse through
rust, cement, concrete	5 - 20	35 - 55 °C	3 - 5 Min.

Please note:

Using the correct dosage reduces costs and protects the environment. Do not combine with other products. Use protective gloves. Please see SDBL on uridan.com. P501 – Dispose of contents/container at an approved waste disposal plant.



Storage instructions:

This product should be stored at room temperature.

Packaging:

6 x 1 liter